

SAFETY DATA SHEET

ACDELCO POWER STEERING FLUID

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

ACDELCO POWER STEERING FLUID

Product no.

19329450 (16 OZ, 473ML)

Unique formula identifier (UFI)

1V00-DOUH-D00S-7RXA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Transmission oil

Uses advised against

The product may only be used in accordance with the area of application specified above. If, nonetheless, the product is used outside the specified scope, please contact the supplier.

1.3. Details of the supplier of the safety data sheet

Company and address

Klintberg & Way Parts AB

Haukadalsgatan 5

164 40 KISTA

Sweden

+46 (0)8 6808800

www.kwparts.com

E-mail

info@kwparts.com

Revision

29-01-2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

May be fatal if swallowed and enters airways. (H304)

Harmful to aquatic life with long lasting effects. (H412)

Safety statement(s)

General

Keep out of reach of children. (P102)

Prevention

Avoid release to the environment. (P273)

Response

Do NOT induce vomiting. (P331)

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)

Storage

-

Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

Hazardous substances

Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]

Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]

Triphenyl phosphate

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]	CAS No.: 64742-53-6 EC No.: 265-156-6 REACH: Index No.: 649-466-00-2	10 - 20%	Asp. Tox. 1, H304	
Paraffin oils (petroleum), catalytic dewaxed	CAS No.: 64742-71-8	5 - 10%	Asp. Tox. 1, H304	

light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]	EC No.: 265-176-5 REACH: Index No.: 649-478-00-8		
Triphenyl phosphate	CAS No.: 115-86-6 EC No.: 204-112-2 REACH: 01-2119457432-41-XXXX Index No.:	< 1%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

No special

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of uncertainty on how to treat an exposed person, call the National Poisons Information Service immediately.

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person’s condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

To avoid irritation flush with soft water jet or eye wash fluid for at least 5 minutes. In case of persistent symptoms (intense burning, pain, sensitivity to light, visual disturbance) continue flushing and contact/seek a hospital or doctor.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER / doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Always wear gloves and protective clothing when in contact with chemical substances.

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A risk assessment of the handling shall always be prepared based on the specific conditions prevailing at the workplace. The risk assessment shall be used as basis for preparing appropriate instructions for the safe handling of the product.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
Triphenyl phosphate
Long term exposure limit (8 hours) (mg/m³): 3
Short term exposure limit (15 minutes) (mg/m³): 6

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	740 µg/kgbw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	1.19 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Local effects - General population

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	970 µg/kgbw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	5.58 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Local effects - Workers

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
DNEL	2.73 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]
DNEL	740 µg/kgbw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]
DNEL	1.19 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Local effects - General population
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]
DNEL	970 µg/kgbw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]
DNEL	5.58 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Local effects - Workers
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]
DNEL	2.73 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	Triphenyl phosphate
DNEL	5,2 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers
Product/substance	Triphenyl phosphate

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

DNEL	5,55 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers
Product/substance	Triphenyl phosphate
DNEL	0,9 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population
Product/substance	Triphenyl phosphate
DNEL	1,98 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population
Product/substance	Triphenyl phosphate
DNEL	525 µg/kgbw/day
Route of exposure	Oral
Duration	Long term – Systemic effects - General population
Product/substance	Triphenyl phosphate
DNEL	525 µg/kgbw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - General population
Product/substance	Triphenyl phosphate
DNEL	910 µg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - General population
Product/substance	Triphenyl phosphate
DNEL	1.05 mg/kg bw/day
Route of exposure	Dermal
Duration	Long term – Systemic effects - Workers
Product/substance	Triphenyl phosphate
DNEL	3.7 mg/m ³
Route of exposure	Inhalation
Duration	Long term – Systemic effects - Workers

PNEC

Product/substance	Distillates (petroleum), hydrotreated light naphthenic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains relatively few normal paraffins.]
PNEC	9.33 mg/kg
Route of exposure	Predators
Duration of Exposure	
Product/substance	Paraffin oils (petroleum), catalytic dewaxed light;Baseoil - unspecified;[A complex combination of hydrocarbons obtained from a catalytic dewxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).]

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

PNEC	9.33 mg/kg
Route of exposure	Predators
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	0,004 mg/L
Route of exposure	Freshwater
Duration of Exposure	Continuous
Product/substance	Triphenyl phosphate
PNEC	5,0 mg/kg
Route of exposure	Sewage treatment plant
Duration of Exposure	Continuous
Product/substance	Triphenyl phosphate
PNEC	1,103 mg/kg dw
Route of exposure	Freshwater sediment
Duration of Exposure	Continuous
Product/substance	Triphenyl phosphate
PNEC	0,11 mg/kg dw
Route of exposure	Marine water sediment
Duration of Exposure	Continuous
Product/substance	Triphenyl phosphate
PNEC	16.667 mg/kg
Route of exposure	Predators
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	28.2 µg/kg
Route of exposure	Soil
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	14.285 µg/kg
Route of exposure	Marine water sediment
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	142.85 µg/kg
Route of exposure	Freshwater sediment
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	5 mg/L
Route of exposure	Sewage treatment plant
Duration of Exposure	
Product/substance	Triphenyl phosphate
PNEC	48 ng/L
Route of exposure	Marine water

Duration of Exposure

Product/substance	Triphenyl phosphate
PNEC	2.5 µg/L
Route of exposure	Intermittent release (freshwater)
Duration of Exposure	

Product/substance	Triphenyl phosphate
PNEC	480 ng/L
Route of exposure	Freshwater
Duration of Exposure	

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

In case of simultaneous exposure to several air pollutants, their combined effects shall be considered. In assessing exposure conditions, the body weight and absorption of certain substances through the skin shall be taken into account in addition to the concentration of air pollutants in inhaled air. The person who plans and carries out the air pollution measurement shall have sufficient knowledge to do so. Measurements shall be taken using appropriate methods and equipment. Exposure measurements relate to conditions during normal operation. Where necessary, they shall also highlight the exposure under other conditions. Exposure measurements shall be taken in the breathing zone on a sufficient number of persons to make it possible to assess the exposure of all exposed persons.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

No specific requirements

Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

Skin protection

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Recommended	Type/Category	Standards
Dedicated work clothing should be worn.	-	-



Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	> 0,4	> 480	EN374



Eye protection

Type	Standards
No specific requirements	-

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Yellowish

Odour / Odour threshold

No data available

pH

Not applicable

Density (g/cm³)

No data available

Relative density

0.88

Kinematic viscosity

No data available

Particle characteristics

Not applicable

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

> 316 °C

Vapour pressure

< 0.013 kPa

Relative vapour density

No data available

Decomposition temperature (°C)

Not applicable

Data on fire and explosion hazards

Flash point (°C)

> 175 °C

Ignition (°C)

No data available

Auto flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility**Solubility in water**

No data available

n-octanol/water coefficient

No data available

Solubility in fat (g/L)

No data available

9.2. Other information**Evaporation rate (n-butylacetate = 100)**

No data available

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

No special

Endocrine disrupting properties

No special

Other information

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

15 01 10* Packaging containing residues of or contaminated by dangerous substances

Specific labelling

Before handling waste, see Section 8, Exposure controls/personal protection. Contamination of the product with hazardous substances during use cannot be ruled out and therefore the properties of the waste do not fully correspond to those of the original product. It is therefore always the user's responsibility to classify the waste.

Hazardous waste shall be transported to an approved waste facility by an authorised carrier.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1. - 14.4.

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

MARINE POLLUTANT

No

IATA

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Restrictions for application**

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Tactile warning.

Sources

The employer is obliged to continuously keep abreast of the current regulations pertaining to the activity in question.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information**Full text of H-phrases as mentioned in section 3**

H304, May be fatal if swallowed and enters airways.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit.
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVCB = Complex hydrocarbon substance
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Future Competence Sweden AB

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en