

SAFETY DATA SHEET

ACDELCO SYNCHROMESH TRANSMISSION FLUID

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

ACDELCO SYNCHROMESH TRANSMISSION FLUID

Product no.

88900333

Unique formula identifier (UFI)

R3C7-86YR-Y88F-V3M1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Transmission Fluid

Uses advised against

The product may only be used in accordance with the area of application specified above. If, nonetheless, the product is used outside the specified scope, please contact the supplier.

1.3. Details of the supplier of the safety data sheet

Company and address

Klintberg & Way Parts AB

Haukadalsgatan 5

164 40 KISTA

Sweden

+46 (0)8 6808800

www.kwparts.com

E-mail

info@kwparts.com

Revision

16-02-2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Causes serious eye irritation. (H319)

Safety statement(s)

General

Keep out of reach of children. (P102)



Prevention

Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

-

Disposal

Hazardous substances

Zinc bis(O,O-diisooctyl) bis(dithiophosphate)

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| Product/substance | Identifiers | % w/w | Classification | Note |
|--|---|----------|--|------|
| Zinc bis(O,O-diisooctyl) bis(dithiophosphate) | CAS No.: 28629-66-5 EC No.: 249-109-7 REACH: 01-2119953278- 28-XXXX Index No.: | 1 -2.49% | Skin Irrit. 2, H315 Eye Dam. 1, H318 (SCL: 15.00 %) Aquatic Chronic 2, H411 | |
| methyl methacrylate;methyl 2- methylprop-2-enoate;methyl 2- methylpropenoate | CAS No.: 80-62-6 EC No.: 201-297-1 REACH: 01-2119452498- 28-XXXX Index No.: 607-035-00-6 | <0.1% | Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 | [1] |
| phenol;carbolic acid;monohydroxybenzene;phenylalcohol | CAS No.: 108-95-2 EC No.: 203-632-7 REACH: 01-2119471329- 32-XXXX Index No.: 604-001-00-2 | 0.0099% | Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 (SCL: 3.00 %) Acute Tox. 3, H331 Muta. 2, H341 STOT RE 2, H373 | [1] |

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available. Other information

[1] European occupational exposure limit

SECTION 4: First aid measures

4.1. Description of first aid measures



General information

In case of uncertainty on how to treat an exposed person, call the National Poisons Information Service immediately.

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Flush with soft water jet or eye wash fluid for at least 5 minutes. In case of persistent symptoms (intense burning, pain, sensitivity to light, visual disturbance) continue flushing and contact/seek a hospital or doctor.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Always wear gloves and protective clothing when in contact with chemical substances.

No specific requirements

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and



place in container for disposal, according to local regulations.

To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A risk assessment of the handling shall always be prepared based on the specific conditions prevailing at the workplace. The risk assessment shall be used as basis for preparing appropriate instructions for the safe handling of the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m³): 208

Short term exposure limit (15 minutes) (ppm): 100

Short term exposure limit (15 minutes) (mg/m³): 416

phenol;carbolic acid;monohydroxybenzene;phenylalcohol

Inhalation

Long term exposure limit (8 hours) (ppm): 2

Long term exposure limit (8 hours) (mg/m³): 7,8

Short term exposure limit (15 minutes) (ppm): 4

Short term exposure limit (15 minutes) (mg/m³): 16

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
|-------------------|--|
| DNEL | 348.4 mg/m³ |
| Route of exposure | Inhalation |
| Duration | Long term – Systemic effects - Workers |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 416 mg/m³ |

Route of exposure



| Duration | Short term – Local effects - Workers |
|-------------------|--|
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 13.67 mg/kg bw/day |
| Route of exposure | Dermal |
| Duration | Long term – Systemic effects - Workers |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 1.5 mg/cm² |
| Route of exposure | Dermal |
| Duration | Long term – Local effects - Workers |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 1.5 mg/cm² |
| Route of exposure | Dermal |
| Duration | Short term – Local effects - Workers |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 74.3 mg/m³ |
| Route of exposure | Inhalation |
| Duration | Long term – Systemic effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 104 mg/m³ |
| Route of exposure | Inhalation |
| Duration | Long term – Local effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 208 mg/m³ |
| Route of exposure | Inhalation |
| Duration | Short term – Local effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 8.2 mg/kg bw/day |
| Route of exposure | Dermal |
| Duration | Long term – Systemic effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 1.5 mg/cm² |
| Route of exposure | Dermal |
| Duration | Long term – Local effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 1.5 mg/cm² |
| Route of exposure | Dermal |
| Duration | Short term – Local effects - General population |
| Product/substance | methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate |
| DNEL | 208 mg/m³ |
| Route of exposure | Inhalation |
| Duration | Long term – Local effects - Workers |



Product/substance methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate

DNEL 8.2 mg/kg bw/day

Route of exposure

Duration Long term - Systemic effects - General population

Product/substance phenol;carbolic acid;monohydroxybenzene;phenylalcohol

DNEL 500 µg/kgbw/day

Route of exposure Oral

Duration Long term - Systemic effects - General population

Product/substance phenol;carbolic acid;monohydroxybenzene;phenylalcohol

500 µg/kgbw/day

Route of exposure Dermal

Duration Long term - Systemic effects - General population

Product/substance phenol;carbolic acid;monohydroxybenzene;phenylalcohol

DNEL 452 μg/m³ Route of exposure Inhalation

Route of exposure

Long term - Systemic effects - General population Duration

Product/substance phenol;carbolic acid;monohydroxybenzene;phenylalcohol

DNEL 1.23 mg/kg bw/day Dermal

Duration Long term - Systemic effects - Workers

phenol;carbolic acid;monohydroxybenzene;phenylalcohol Product/substance

DNFI 16 mg/m³ Inhalation Route of exposure

Duration Short term - Local effects - Workers

Product/substance phenol;carbolic acid;monohydroxybenzene;phenylalcohol

DNEL 8 mg/m³ Route of exposure Inhalation

Long term - Systemic effects - Workers Duration

PNEC

Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate)

PNEC 4 µg/L Route of exposure Freshwater Continuous **Duration of Exposure**

Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate)

PNEC 4.6 µg/L Route of exposure Marine water Continuous **Duration of Exposure**

Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate)

PNEC 3 mg/L

Route of exposure Sewage treatment plant

Duration of Exposure Continuous



Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate) **PNEC** 0.144 mg/kg sediment dw Freshwater sediment Route of exposure **Duration of Exposure** Continuous Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate) **PNEC** 0.014 mg/kg sediment dw Route of exposure Marine water sediment **Duration of Exposure** Continuous Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate) **PNEC** 0.026 mg/kg soil dw Route of exposure Soil **Duration of Exposure** Continuous Product/substance Zinc bis(O,O-diisooctyl) bis(dithiophosphate) **PNEC** 8.33 mg/kg food Route of exposure **Predators** Continuous **Duration of Exposure** Product/substance methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate **PNEC** 1.48 mg/kg Soil Route of exposure **Duration of Exposure** Product/substance methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate **PNFC** 102 µg/kg Marine water sediment Route of exposure **Duration of Exposure** Product/substance methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate **PNEC** 10.2 mg/kg Route of exposure Freshwater sediment **Duration of Exposure** Product/substance methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate **PNEC** 10 mg/L Route of exposure Sewage treatment plant **Duration of Exposure** Product/substance methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate **PNEC** 94 µg/L Marine water Route of exposure **Duration of Exposure** Product/substance methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate **PNEC** 940 µg/L Intermittent release (freshwater) Route of exposure **Duration of Exposure** Product/substance methyl methacrylate;methyl 2-methylprop-2-enoate;methyl 2-methylpropenoate **PNEC** 940 µg/L



| Route of exposure Duration of Exposure | Freshwater |
|--|---|
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 136 μg/kg Soil |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 9.15 µg/kg Marine water sediment |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 91.5 µg/kg Freshwater sediment |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 2.1 mg/L Sewage treatment plant |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 770 ng/L Marine water |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 31 μg/L Intermittent release (freshwater) |
| Product/substance PNEC Route of exposure Duration of Exposure | phenol;carbolic acid;monohydroxybenzene;phenylalcohol 7.7 μg/L Freshwater |

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

In case of simultaneous exposure to several air pollutants, their combined effects shall be considered. In assessing exposure conditions, the body weight and absorption of certain substances through the skin shall be taken into account in addition to the concentration of air pollutants in inhaled air. The person who plans and carries out the air pollution measurement shall have sufficient knowledge to do so. Measurements shall be taken using appropriate methods and equipment. Exposure measurements relate to conditions during normal operation. Where necessary, they shall also highlight the exposure under other conditions. Exposure measurements shall be taken in the breathing zone on a sufficient number of persons to make it possible to assess the exposure of all exposed persons.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See



occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

| Type | Class | Colour | Standards | |
|---|---|-------------|-----------------------------------|--|
| Respiratory protection is not needed in the event of adequate ventilation | - | - | - | |
| Combination filter A + P3 | If there is a risk of exposure to vapor or aerosol, use combination filter against organic gases and vapors (type A), and particulate filter (type P3). | Brown/White | P3 (EN 140, EN 143, EN 149) | |

Skin protection

| Recommended | Type/Category | Standards | |
|--|---------------|-----------|--|
| Dedicated work clothing should be worn | - | - | The state of the s |

Hand protection

| Material | Glove thickness (mm) | Breakthrough time (min.) | Standards | |
|----------|----------------------|--------------------------|-----------|--|
| Nitrile | > 0,4 | > 480 | EN374 | |

Eye protection

| Туре | Standards | |
|--|-----------|--|
| Wear safety glasses with side shields. | EN166 | |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Testing not relevant or not possible due to nature of the product.

Odour / Odour threshold

Faint

рΗ



No data available

Density (g/cm³)

No data available

Relative density

0.897

Kinematic viscosity

40 centistokes

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

No data available

Vapour pressure

< 0.5 Pa (20 °C)

Relative vapour density

No data available

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Data on fire and explosion hazards

Flash point (°C)

350

Ignition (°C)

No data available

Auto flammability (°C)

No data available

Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient

No data available

Solubility in fat (g/L)

No data available

9.2. Other information

Other physical and chemical parameters

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, bases, oxidizing agents and reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.



SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

No special

Other information

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.

SECTION 12: Ecological information

12.1. Toxicity

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

No special

12.7. Other adverse effects

The assessment of the properties of the constituents is based primarily on information in the ECHA database of registered substances, and the classification and labelling register.



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

15 01 10* Packaging containing residues of or contaminated by dangerous substances

Specific labelling

Before handling waste, see Section 8, Exposure controls/personal protection. Contamination of the product with hazardous substances during use cannot be ruled out and therefore the properties of the waste do not fully correspond to those of the original product. It is therefore always the user's responsibility to classify the waste. Hazardous waste shall be transported to an approved waste facility by an authorised carrier.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

14.1. - 14.4.

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

Not applicable

IMDG

Not applicable

MARINE POLLUTANT

No

IATA

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

Not applicable

Additional information

Not applicable

Sources

The employer is obliged to continuously keep abreast of the current regulations pertaining to the activity in question.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment



No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H301, Toxic if swallowed.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H331, Toxic if inhaled.

H335, May cause respiratory irritation.

H341, Suspected of causing genetic defects.

H373, May cause damage to organs through prolonged or repeated exposure.

H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol

of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP)

The safety data sheet is validated by

Future Competence Sweden AB

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en